







Hybrid Inverter

SUN-3/3.6/5/6K-SG04LP1-EU



-  Colorful touch LCD, IP65 protection degree
-  AC couple to retrofit existing solar system
-  Max. 16 pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel
-  Max. charging/discharging current of 140A
-  6 time periods for battery charging/discharging
-  Support storing energy from diesel generator

Deye

Stock Code: 605117.SH

Model	SUN-3K -SG04LP1-24-EU	SUN-3K -SG04LP1-EU	SUN-3.6K -SG04LP1-EU	SUN-5K -SG04LP1-EU	SUN-6K -SG04LP1-EU
Battery Input Data					
Battery Type	Lead-acid or Lithium-ion				
Battery Voltage Range (V)	20-30	40-60	40-60	40-60	40-60
Max. Charging Current (A)	140	70	90	120	135
Max. Discharging Current (A)	140	70	90	120	135
External Temperature Sensor	Yes				
Charging Curve	3 Stages / Equalization				
Charging Strategy for Li-Ion Battery	Self-adaption to BMS				
PV String Input Data					
Max. DC Input Power (W)	3900	3900	4680	6500	7800
Rated PV Input Voltage (V)	370 (125-500)				
Start-up Voltage (V)	125				
MPPT Voltage Range (V)	150-425				
Full Load DC Voltage Range (V)	300-425				
PV Input Current (A)	13		13+13		
Max. PV I _{SC} (A)	17		17+17		
No.of MPP Trackers	1		2		
No.of Strings per MPP Tracker	1		1+1		
AC Output Data					
Rated AC Output Active Power (W)	3000		3600	5000	6000
Max AC Output Active Power (W)	3300		3960	5500	6600
AC Output Rated Current (A)	13.6/13		16.4/15.7	22.7/21.7	27.3/26.1
Max. AC Current (A)	15/14.3		18/17.2	25/23.9	30/28.7
Max. Continuous AC Passthrough (A)	35				40
Peak Power (off grid)	2 time of rated power, 10 S				
Power Factor Adjustment Range	0.8 leading to 0.8 lagging				
Power Factor	1				
Output Frequency and Voltage	50/60Hz; L/N/PE 220/230Vac				
Grid Type	Single Phase				
Total Harmonic Distortion (THD)	<3% (of nominal power)				
DC Current Injection	<0.5% I _n				
Efficiency					
Max. Efficiency	97.60%				
Euro Efficiency	96.50%				
MPPT Efficiency	99.90%				
Protection					
Integrated	Anti-islanding Protection, PV String Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection, Surge Protection				
Over Voltage Category	DC Type II/AC Type III				
Certifications and Standards					
Grid Regulation	VDE4105, IEC61727/62116, VDE0126, AS4777.2, CEI 0 21, EN50549-1, G98, G99, C10-11, UNE217002, NBR16149/NBR16150				
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				
General Data					
Operating Temperature Range ()	-40-60°C, >45°C Derating				
Cooling	Free Cooling				Smart Cooling
Noise (dB)	≤30 dB				
Communication with BMS	RS485; CAN				
Weight (kg)	14			15.1	
Cabinet Size (WxHxD mm)	330×433×238 (Excluding Connectors and Brackets)				
Protection Degree	IP65				
Installation Style	Wall-mounted				
Warranty	5 Years (10 Years Optional)				